



Welding inverter TIG 200i AC/DC

TIG 200i AC/DC is equipped with:

- Compact and portable digital inverter for TIG welding with HF or Lift arc start and MMA
- Self-saving and recalling function on welding data
- PFC technology
- AC/DC technology
- Durable and impact resistance design
- Single knob and contact control panel, precise and Adjustable welding data, easy to operate
- Welds electrodes from ø 1,6 4,0 mm
- Capable to work on generator power source
- Over current protection / Over voltage protection
- Adjustable slope up/down and gas pre / post flow to control starts and avoid cracks and oxidationat the end

Pulsed TIG welding

TECHNICAL DATA

Order No.: 0302006018
Order No.: 0302006018 MAIN SUPPLY (V/Ph Hz) 110V/230V 50HZ
Input Voltage Tolerance (%)±15
Input power (kVA) 5.26
SETTING RANGE (A) 10-200
MAX. OUTPUTS AT 35%/20% DUTY CYCLE, A (MMA)80/160
MAX. OUTPUTS AT 60% DUTY CYCLE, A (MMA)
MAX. OUTPUTS AT 100% DUTY CYCLE, A (MMA) 47/72
MAX. OUTPUTS AT 30%/20% DUTY CYCLE, A (TIG)120/200
MAX. OUTPUTS AT 60% DUTY CYCLE, A (TIG)
MAX. OUTPUTS AT 100% DUTY CYCLE, A (TIG) 71/89
Open-circuit voltage 60
Maximum current draw (IEFF) 13/9.8
Electrode Sizes Dia. 4
2T-4T settings for torchyes
Pre/Post Gas Fuctionves
DIMENSIONS (LxBxH mm) 538x241x402
WEIGHT of the machine (kg)22.7





STANDARD EQUIPMENT:

- welding cable
 - TIG torch
- returne cable
- mask & brush